

Century Machinery Co., Inc.

1937 South Santa Fe Avenue Los Angeles, Calif. 90021

(213) 627-2847 • Fax (213) 627-2499

E-Mail: sales@centurymachinery.com

WEBSITE: www.centurymachinery.com

Ref. Number B1804-7117

- Air Compressor
- C.N.C. Machine Tools
- Fabricating Equipment
- Fluid Forming Press
- Industrial Machinery
- Machine Tools
- Profilers 3 and 5 Axis
- Routers: Pin, Radial & CNC
- Sheet Metal Machinery
- Woodworking Machinery

Appraisal Service

"WE PURCHASE ONE MACHINE OR ENTIRE PLANT"

Serving Industry Since 1934



WALLACE TUBE, PIPE BENDER

Model 500-3, Type: Rotary Draw, Serial Number 1002007, Date Mfg. 7/73

Condition: All Hydraulic Pump and Valves Rebuilt.

SPECIFICATIONS

CAPACITY BEND:

Tubing Steel, 1010/1020, O.D. x Wall	3" X .095"
I.P.S	2" X H
Tubing Non-Ferrous, 12Klb.Yield, O.D. x Wall	5" x 1/8"
Tubing Non-Ferrous, 25Klb. Yield, O.D. x Wall	5" x 0.83"
Square Tubing, Steel 1010/1020, Size x Wall	2" x 1/8"
Angles, Equal Leg (2 at a time), Legs x Thickness	2" x 3/8"
I-Beam Hard Way, Size x Wt.	4" x 9.5 lbs.
Flat Steel 1010/1020: Hard Way..... 3/8" x 2 1/4". Easy Way	3/8" x 5"
Flat, Non-Ferrous: 25Klb. Hard Way..... 3/8" x 3" Easy Way	3/8" x 4"
Round Bar Steel 1010/1020..... 1 1/4" Square Steel 1010/1020	1 3/8"

BEND RADIUS ADJUSTMENT to Centerline, (Angle Maximum) 24"

Extended Radius Adjustment

ARM ROTATION, Counter Clockwise, Horizontally thru 180° Arc

MANDREL EXTRACTOR: Hydraulic

Stroke Length..... 15"

Clear Load Length..... 12'-6"

Power Oscillating. Side Adjustment powered by geared motor drive.

FOLLOWER and CLAMP DIE TOGGLE LEVERS: (Automatic Operation)

MOTOR DRIVE: *Wired 220 volts, 3 phase*

Hydraulic Pumps

Booster Pump..... 5 H.P. 220/440 volts

Oscillation Geared Drive

Mandrel Power Cross Movement Geared Drive..... 1/4 H.P. 220/440 volts

OPERATORS CONTROLS STATION: Free Standing *Controls Wired Low Voltage*

Start/Stop Buttons. Manual and Auto Switch. Safety Pressure Shut Off Switch on Bend Arm.

Press Die In/Out. Clamp In/out. Arm Forward/Return. Mandrel In/Out.

Mandrel Oscillation On / Off Switch. Mandrel Carriage Cross Movement Forward / Back Buttons.

EQUIPPED WITH: Degree of Bend with 8 stops. Plain of Bend with 6" diameter 3-Jaw Chuck.

8- Carriage Flip Stops. Pressure Die Booster. Mandrel Oscillation. 1- Die Post 1 1/4" diameter.

Wiper Die Support Bracket with vertical and Horizontal and axial adjustment . 1- Radius Die 2 1/2"

1-Pressure Die 2 1/2" diameter. 1-Clamp Die 2 1/2" diameter x 24" long. 1- Wiper Die 2 1/2".

1- Mandrel Rod. 1-Mandrel 2 1/2" diameter. Mandrel Oiler.

COMPLETE FACTORY SAFETY GUARDS

PLEASE EMAIL US YOUR REQUEST FOR A FORMAL QUOTATION WITH PRICE

AT sales@centurymachinery.com

Please use this inventory reference number B7015-9730

<http://www.centurymachinery.com/request form.htm>

You may view this machine at our location under power and view photo on our website: www.centurymachinery.com

Respectfully submitted,

CENTURY MACHINERY CO., INC.